

ELECTRIFICATION OF MILWAUKEE BRANCH  
OF THE  
CHICAGO AND NORTHWESTERN RAILWAY

BY

H. L. CASE  
F. FERNANDEZ - MAREQUE  
A. F. SCHOEMBS  
R. W. WHITMORE

ARMOUR INSTITUTE OF TECHNOLOGY

1914

621.33  
C 26



**Illinois Institute  
of Technology  
UNIVERSITY LIBRARIES**

AT 325

Case, H. L.

Proposed electrification of  
the Milwaukee branch,

**For Use In Library Only**



PROPOSED ELECTRIFICATION  
of  
THE MILWAUKEE BRANCH  
CHICAGO & NORTHWESTERN RAILWAY

A THESIS

PRESENTED BY

H. L. Case  
F. Fernandez-Mareque  
A. F. Schoombs  
R. W. Whitmore

TO THE

PRESIDENT AND FACULTY

OF

ARMOUR INSTITUTE OF TECHNOLOGY

FOR THE DEGREE OF

BACHELOR OF SCIENCE IN ELECTRICAL ENGINEERING

HAVING COMPLETED THE PRESCRIBED COURSE OF STUDY IN

ELECTRICAL ENGINEERING

May 1914

Approved  
E. H. Freeman  
Professor of Electrical Engineering  
H. M. Raymond  
L. C. Morin



C O N T E N T S.

Introduction - - - - -	page, 1
The Speed-time Curve - - - - -	2
Choice of acceleration - - - - -	2
Car weight - - - - -	8
Choice of motors and gear ratio -	8
Schedule - - - - -	17
Cars and Equipment - - - - -	19
Distribution System - - - - -	20
Spot map - - - - -	20
Trolley section - - - - -	20
Number of substations - - - - -	21
Location of substations - - - - -	22
Feeders. - - - - -	22
Substations - - - - -	23
General description - - - - -	23
Operation - - - - -	24
Specifications - - - - -	25
Transmission Line - - - - -	28
Choice of wire - - - - -	28
Capacity and inductance - - - - -	31
Natural period of the line - - - -	32





Transmission Line (Cont'd)

Power house voltage - - - - -	page, 33
Regulation - - - - -	34
Charging current, etc - - - - -	33
Power House - - - - -	35
Location - - - - -	35
Power curve - - - - -	35
Equipment - - - - -	36
Switchboard - - - - -	39



## INTRODUCTION.

This thesis covers in a brief way, the design of a complete railway installation for the proposed "Electrification of the Chicago-Milwaukee Branch of the Chicago and Northwestern Railway".

We have attempted to indicate a general method of procedure, including sample calculations and conclusions drawn therefrom; estimate the cost of the installation and maintenance; and compute the net earnings of the proposed system.

In the preparation of this thesis many valuable suggestions have been made by Professors Freeman, Snow, and Nichols, of the Armour Institute of Technology.

No attempt has been made to enter into the details of all or any particular portion of the design. Such a task as a detail design could only be accomplished by a Board of Engineers with at least two or three years time to devote to the subject.

MEMORANDUM

TO : THE PRESIDENT

FROM : THE SECRETARY OF STATE

SUBJECT: [Illegible]

[The following text is extremely faint and illegible due to the quality of the scan. It appears to be a memorandum with several paragraphs of text.]

## THE SPEED TIME CURVE.

In the preliminary calculation and determination of the speed-time curve the following factors have been considered:

- (a) Choice of acceleration, involving distance between stops, the average speed, and weight of car.
- (b) The profile of the line.
- (c) Choice of motor and gear ratio.
- (d) Frequency of the service.

### Choice of Acceleration.

The general solution of the problem is here considered because of its important relation to the choice of motors, a factor which directly determines the initial cost of the entire system.

Referring to Fig. 1, an arbitrarily assumed straight line speed-time curve for a straight and level track, the following notation has been used:

- a - Acceleration in miles per hour per second along OA ( $=DA+OD$ )









- b - Retardation during braking ( $=Ab+ED$ )
- c - Retardation during coasting ( $=BE+EC$ )
- x - Time required to go from O to A. ( $=OD$ )
- y - Time for AB ( $=DE$ )
- z - Time for BC ( $=EC$ )
- $s_1$  - Distance for OA. ( $=\text{Area OAD}$ )
- $s_2$  - Distance for AB. ( $=\text{Area DABE}$ )
- $s_c$  - Distance for BC. ( $=\text{Area EBC}$ )
- T - Total time of run. ( $=OC$ )
- L - Total distance. ( $=\text{Area OABC}$ )
- V - Average velocity. ( $=0.682 L+T$ ) ( one  
mile per hour = 0.682 feet per second)

As indicated in the figure the car is assumed to be moving with a constant acceleration up to its maximum speed for a time OD, then is retarded at a constant coasting rate for a time DE, and finally is retarded during braking at a constant acceleration over a period of time equal to EC.

The velocities, times, and distances referred to in the foregoing discussion may be represented by the three following equations:



$$(1) ax - by - cz = 0$$

$$(2) x + y + z = T$$

$$(3) ax^2 - by^2 + cz^2 + 2axy = 2 \times 0.682 L.$$

$$\text{Put: } \frac{x}{T} = \xi ; \frac{y}{T} = \eta ; \frac{z}{T} = \zeta$$

$$\text{Then: } \xi + \eta + \zeta = 1$$

$$a\xi - c\eta - b\zeta = 0$$

$$a\xi^2 - a\xi\eta + b\eta^2 + b\zeta^2 = 2 \frac{L}{T^2} = 2A$$

$$\text{Where } A = 0.682 \frac{L}{T^2}.$$

$$\eta = \frac{b - (b+a)\xi}{b-c}$$

$$\zeta = \frac{(a+c)\xi - c}{b-c}$$

" $\xi$ ", is now found in terms of "a" and "A".


This is accomplished by assuming average values for coasting and braking as 0.15 and 2.0, respectively, substituting same in the preceding equations, and solving for  $\xi$  for different values of "A" and "a". The results of such a calculation are shown by the curves of Fig. 2.

By use of the general equations of the speed-time curve, table 1 was calculated, a sample of the procedure being given below:

$A = 0.682 \frac{L}{T^2}$ , where L is the average length of run, a factor which was determined



Fig 2





T A B L E 1.

a	A	T	S	x	w-70	KW./ton	
1.0	.15	175.9	24.30	38.7	48.9	4.08	.220
	.20	152.3	27.70	43.3	61.2	4.57	.284
	.25	136.1	30.70	49.4	79.8	5.21	.363
	.30	124.3	33.30	59.3	114.8	6.26	.477
	.35	115.1	35.65	----	----	----	----
	.40	107.6	37.90	----	----	----	----
	.45	101.5	39.80	----	----	----	----
	:	:	:	:	:	:	:
	:	:	:	:	:	:	:
1.5	.15	175.9	24.30	26.7	50.2	6.06	.152
	.20	152.3	27.70	28.9	58.7	6.56	.190
	.25	136.1	30.70	31.9	71.3	7.25	.234
	.30	124.3	33.30	35.0	86.1	7.95	.282
	.35	115.1	35.65	39.4	108.7	8.95	.342
	.40	107.6	37.90	47.0	155.0	10.67	.437
	.45	101.5	39.80	----	----	----	----
	:	:	:	:	:	:	:
	:	:	:	:	:	:	:
2.0	.15	175.9	24.30	19.87	47.9	7.80	.113
	.20	152.3	27.70	21.00	53.5	8.25	.138
	.25	136.1	30.70	23.15	65.1	9.10	.170
	.30	124.3	33.30	25.30	77.4	9.94	.203
	.35	115.1	35.65	27.18	89.6	10.68	.236
	.40	107.6	37.90	31.10	117.5	12.24	.289
	.45	101.5	39.80	36.20	159.3	14.22	.357





following an investigation of the number of stops and the distance between same. The particular run under consideration was chosen as that between Chicago and Waukegan, because the maximum traffic occurs between these two points.

$$\text{Then } 0.682 L = 4640$$

Then from curve of Fig. 2, for  $A = .15$  and  $a = 1$

$$T = \sqrt{\frac{4640}{.15}} = 175.9$$

$S =$  miles per hour  $= \frac{0.682 L}{T + \tau}$ , where  $\tau$  is the stopping time (-15 seconds).

$$\text{Therefore } S = \frac{4640}{175.9 + 15} = 24.3$$

$$X = \int T = .220 \times 175.9 = 38.7$$

( $\int$  obtained from curve.)

$W_{70} =$  Watts per ton mile at 70% efficiency.

$$W_{70} = \frac{[91.1a^2 + fa]^c}{0.7 A} = 48.9$$

$f =$  Lbs. friction per ton = 15.

$$\text{KW/ton} = \frac{[91.1a + \frac{2X}{2}] \cdot 1.47 \cdot 0.746}{550} = 4.08$$

After a careful study of Table 1, an acceleration of 1.5 with a running time of 136.1 seconds was chosen as being the most economical acceleration and time of run.



### Choice of Motors and Gear Ratio.

From practical operating conditions of roads similar to the one under consideration the car weight including 62 passengers was set at 45 tons. The motor capacity was estimated at about 460 H.P., equally divided among four motors.

Of the various motors considered the 303A Westinghouse Railway Motor was found best adapted to the conditions. This conclusion was arrived at as follows: the performance curves of the given motor were plotted for different values of gear ratio, as shown in Figs. 3, 4, and 5; the data being obtained from the manufacturer. From the appearance of a few preliminary speed-time curves, the time of run was set at 140 seconds. A sample calculation and outline of the method employed in plotting the speed-time curve is given below:

Straight and level track assumed.

Given:

Gear ratio=2.21;  $a=1.5$ ;  $f=15$ ; car weight



of 45 tons; 4 - 115 H.P. motors.

Therefore, tons per motor =  $45 \div 4 = 11.25$

Since  $91.1a = p - f$ , where  $p \ni$  Lbs. tractive effort per ton,

Then  $91.1 \times 1.5 = p - 15$ .

Or,  $p = 151.7$  Lbs. per ton.

From the motor curve for a tractive effort of  $1710 = 151.7 \times 11.25$ ,  $I$  is found to be 182 amperes. Then when  $I = 182$  amperes,  $V = 27.5$  (from Fig. 4).

It is evident that by varying the current supplied to the motor, the tractive effort can be kept constant up to a speed of 27.5 miles per hour, at which time the motor will operate according to its characteristic. The accelerating portion of the curve was then drawn; it being a straight line up to 27.5. A sample calculation for the motor curve is given below and the data used in plotting the curve is given in Fig. 2.

$$dt = \frac{91.1 dv}{p - f} = \frac{91.1 \times 2.5}{106.7 - 15} = 2.48$$

$dv$ , assumed at 2.5, then  $V = 27.5 + 2.5 = 30$ .

When  $V = 30$ ,  $p = \frac{P}{11.25} = \frac{1200}{11.25} = 106.7$ ; ( $P$  taken from

tractive effort curve).



Fig. 3  
 Performance Curves  
 of  
 Westinghouse  
 507A Railway Motor  
 Ratio 3:81








Fig 4  
 Performance Curves  
 of  
 Westinghouse  
 309 A Railway Motor  
 Ratio 2:21







Fig 5  
 Performance Curves  
 of  
 Westinghouse  
 303 A Railway Motor  
 Ratio 2.95











Fig. 6  
PRELIMINARY  
SPEED TIME CURVES







T A B L E 2.

dv	:	V	:	dt	:	t
.	:	27.5	:	----	:	18.3
2.5	:	30.0	:	2.48	:	20.78
3.0	:	33.0	:	4.20	:	24.98
3.0	:	36.0	:	5.80	:	30.78
3.0	:	39.0	:	7.14	:	37.92
3.0	:	42.0	:	9.85	:	47.77
3.0	:	45.0	:	12.20	:	59.97
3.0	:	48.0	:	18.00	:	77.97
3.0	:	51.0	:	37.90	:	115.87
3.0	:	54.0	:	<b>97.50</b>	:	213.37

# TABLE I

Year	1910	1911	1912
1910	100	100	100
1911	100	100	100
1912	100	100	100
1913	100	100	100
1914	100	100	100
1915	100	100	100
1916	100	100	100
1917	100	100	100
1918	100	100	100
1919	100	100	100
1920	100	100	100
1921	100	100	100
1922	100	100	100
1923	100	100	100
1924	100	100	100
1925	100	100	100
1926	100	100	100
1927	100	100	100
1928	100	100	100
1929	100	100	100
1930	100	100	100
1931	100	100	100
1932	100	100	100
1933	100	100	100
1934	100	100	100
1935	100	100	100
1936	100	100	100
1937	100	100	100
1938	100	100	100
1939	100	100	100
1940	100	100	100
1941	100	100	100
1942	100	100	100
1943	100	100	100
1944	100	100	100
1945	100	100	100
1946	100	100	100
1947	100	100	100
1948	100	100	100
1949	100	100	100
1950	100	100	100
1951	100	100	100
1952	100	100	100
1953	100	100	100
1954	100	100	100
1955	100	100	100
1956	100	100	100
1957	100	100	100
1958	100	100	100
1959	100	100	100
1960	100	100	100
1961	100	100	100
1962	100	100	100
1963	100	100	100
1964	100	100	100
1965	100	100	100
1966	100	100	100
1967	100	100	100
1968	100	100	100
1969	100	100	100
1970	100	100	100
1971	100	100	100
1972	100	100	100
1973	100	100	100
1974	100	100	100
1975	100	100	100
1976	100	100	100
1977	100	100	100
1978	100	100	100
1979	100	100	100
1980	100	100	100
1981	100	100	100
1982	100	100	100
1983	100	100	100
1984	100	100	100
1985	100	100	100
1986	100	100	100
1987	100	100	100
1988	100	100	100
1989	100	100	100
1990	100	100	100
1991	100	100	100
1992	100	100	100
1993	100	100	100
1994	100	100	100
1995	100	100	100
1996	100	100	100
1997	100	100	100
1998	100	100	100
1999	100	100	100
2000	100	100	100
2001	100	100	100
2002	100	100	100
2003	100	100	100
2004	100	100	100
2005	100	100	100
2006	100	100	100
2007	100	100	100
2008	100	100	100
2009	100	100	100
2010	100	100	100
2011	100	100	100
2012	100	100	100
2013	100	100	100
2014	100	100	100
2015	100	100	100
2016	100	100	100
2017	100	100	100
2018	100	100	100
2019	100	100	100
2020	100	100	100
2021	100	100	100
2022	100	100	100
2023	100	100	100
2024	100	100	100
2025	100	100	100
2026	100	100	100
2027	100	100	100
2028	100	100	100
2029	100	100	100
2030	100	100	100
2031	100	100	100
2032	100	100	100
2033	100	100	100
2034	100	100	100
2035	100	100	100
2036	100	100	100
2037	100	100	100
2038	100	100	100
2039	100	100	100
2040	100	100	100
2041	100	100	100
2042	100	100	100
2043	100	100	100
2044	100	100	100
2045	100	100	100
2046	100	100	100
2047	100	100	100
2048	100	100	100
2049	100	100	100
2050	100	100	100

The braking line was then drawn with a slope of 2.0, in such a position as to meet the time axis at 140. The coasting line of slope 0.15 was placed in such a manner that the area of the curve was equal to the length of the run.

Curves for the other two gear ratios were plotted in a similar manner and it was found that the motor with a ratio of 3.81 could not make the run in the required time. The problem was then reduced to a selection of one of the two remaining ratios.

The final choice was made by plotting current curves for each gear ratio, and as can be seen from Fig. 6, the motor with a gear ratio of 2.85 consumed the smaller amount of power. The mean effective value of current was calculated and as this came within the continuous rating of the motor and at the same time was not too low, a factor which would condemn the motor as being too large, the motor of 2.85 ratio was chosen.

The type of motor having been decided upon



the final speed-time curves were plotted and are shown on Plates 1 and 2. The calculations for these curves are the same as those mentioned heretofore, with the exception that retarding forces due to grades and curves were considered, same being obtained from the profile of the line. The retarding or accelerating force "G" due to grades, depending on whether the grade is positive or negative, was taken as 200 times the per cent grade; and the retarding force per ton due to curves was set as 0.5 x the degree of curvature. A general equation is:

$$91.1a = p - f - G - C.$$

In case the car is to be started on an up-grade the value of "a" must be calculated because the acceleration for a level track was set at 1.5 and the rheostat was designed accordingly, therefore the starting torque per ton is not to be greater than 151.7, as computed for a straight and level track. The value of "a" for any condition is readily determined by substituting the values of p, f, G, and C in the above equation.

Faint, illegible text at the top of the page, possibly a header or introductory paragraph.

Main body of faint, illegible text, appearing to be several lines of a letter or document.

Lower section of faint, illegible text, possibly a signature block or concluding remarks.

Faint text at the bottom of the page, possibly a footer or page number.

The curves as plotted are for a 600 volt 303A motor, therefore since the series-parallel operation is to be used with a trolley voltage of 1200, the current per car is given by the current curve for such times as all motors are in series. At other points the current per car is twice that shown by the curve.

THE UNIVERSITY OF CHICAGO  
DEPARTMENT OF CHEMISTRY  
58 CHEMISTRY BUILDING  
CHICAGO, ILLINOIS 60637  
TEL: 773-936-3700  
FAX: 773-936-3701  
WWW: WWW.CHEM.UCHICAGO.EDU



## SCHEDULE.

The traffic over the line having been well established for operation as a steam road the matter of drawing up a schedule for the proposed system was a more or less simple matter. Conditions of traffic operation were considered with the General Passenger Agent of the road and our conclusion as to the best schedule to be followed is indicated on plates 3 and 4. The trains to be operated in accordance with this schedule consist of seven cars for all trains from Chicago to Milwaukee or vice versa; five cars for the Chicago-Waukegan and intermediate, and of two cars for the Kenosha-Milwaukee service.

Without doubt it is true that it would, if possible, be better to have a more frequent schedule of fewer cars per train thus making a saving in the first cost of the feeder system, but upon investigation it was found that the traffic at the present time and for some time to come was of such a nature that trains made

of the ... ..

... ..

... ..

... ..

up of several cars would be required for all  
through trains to Milwaukee.

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

### CARS AND EQUIPMENT.

The cars suggested, are those of The McGuire-Cummings Manufacturing Company's standard type passenger coach with a seating capacity of 62 persons, equipped with four 600 volt 303A, Westinghouse Railway Motors. The motors gear drive to 33-inch wheels with a ratio of 2.85 . The starting equipment is to be that of the Westinghouse multiple-unit control system. The general specifications for car and equipment are the same as those adopted by the American Car Builders Association. The estimated cost of car complete with equipment, was set at \$9000.

THE HISTORY OF THE

REIGN OF KING CHARLES THE FIRST

By JOHN BURNET, BISHOP OF SALISBURY.

IN TWO VOLUMES.

LONDON, Printed by J. Sturges, at the Black-Swan in St. Dunstons Church; and by J. Smith, in Strand, 1724.

## DISTRIBUTION SYSTEM.

### Spot Map.

On inspection of the schedule, speed-time and power curves it was found that the maximum load occurred between 7:40 A.M. and 8:30 A.M. A spot map as shown on Plate 5 was then plotted, the total length divided into 28 sections and the average number of cars per section noted. The current per section was calculated on the assumption that each car consumed 100 amperes as an average value. It will be noted that the sum of all the average number of cars when multiplied by 100 amperes is equal to the maximum current indicated by the power curve; therefore it is evident that the spot map represents an average maximum condition.

### Substations.

The number of substations for the system was determined by means of the following equation:\*

$$\lambda^2 = \frac{n^2 W^2 L + k_1 k_2 f^2 m L}{1.771 I_0 V p m k_2 C_2 C_3 + \frac{P^2 (C_1 g_2 h)}{L m}} \text{ feet}$$

\*(From "Electric Traction and Transmission Engineering", Sheldon & Hausman - P.186.)





$n'$  - attendants per station - - - - - 3  
 $w'$  - attendants salary per year - - - \$800.  
 $L$  - length of road in feet - - - - 446,910  
 $p_3$  - annual rate covering interest - \$0.15  
 $f'_3$  - cost constant - - - - - 4600  
 $u$  - number of units - - - - - 3  
 $I_0$  - mean effective amperes per foot .015  
- conductor resistance in ohms - - - 10  
 $w$  - weight per mil-foot in lbs.- .00000303  
 $p_2$  - annual charge against the  
contact conductor - - - - - \$0.06  
 $c_2$  - cost of conductor per lb. - - - \$0.16  
 $c_3$  - cost of power per kilowatt hour  
delivered from substation - - - \$0.01  
 $P$  - maximum capacity  
- rated installed capacity  $\frac{P^2}{2} = 20,000$   
 $c'_3$  - cost /kW Hr delivered to substation  
\$0.01  
 $g_3$  - constant for conversion.  
 $h$  - equivalent annual hours of operation.



The solution of the equation resulted in the choice of seven substations.

#### Location of Substations.

The trolley sections previously decided upon were divided into seven parts and the proper location of the substations determined by finding the center of gravity of each division. The current per trolley section was considered as a mechanical load. As a result of this scheme the most economical location of the stations, in thousand feet from Chicago, were found to be: 24.5; 70.6; 115.0; 178.0; 262.0; 350.0; and 418.0

The location of the substations having been decided upon the size of the feeders was calculated on a basis of a 200 volt drop between station bus and end of any feeder. The sizes of positive feeders for one substation are shown on Plate 6.



## SUBSTATIONS.

### General Description.

The seven substations previously decided upon are suggested as being of the rotary converter type of 2000 K.W. rated capacity. Each station is to be equipped with three six-phase 1000 K.W. General Electric synchronous converters connected to switch gear apparatus in such a manner that any two of the machines can be operated in series on the direct current side. The alternating current end of each rotary is to be connected to a bank of three single phase oil cooled Allis-Chalmers transformers, delta connected on both high and low tension sides. The oil switches connecting the transformers with the high tension bus are to be of the General Electric H<sub>6</sub> type. The one extra converter has been supplied in insure continuous service. The lightning arresters and choke coils have been so chosen and arranged as to give ample protection from storm disturbances.



### Operation.

In connection with the starting apparatus of the synchronous converter a field breakup and reversing switch is to be mounted on the frame of each machine. At the moment the machine is connected to the alternating current side, the field switch must be open. The converter being started as an ordinary induction motor by varying the impressed voltage by means of a three pole double throw switch connected to low voltage taps of the transformers as indicated in the wiring diagram.

Full voltage is not to be applied to the machine until the polarity has been determined. As soon as the rotary has nearly reached synchronism, the voltmeter which is located on the switchboard and connected across the direct current terminals of the machine, will indicate the polarity of the apparatus. In case the polarity happens to be the one desired the field switch is closed and the full alternating voltage applied. In case the direct voltage builds up





reversed the field switch is thrown to the reversed position. This operation causes the field flux to oppose the armature flux with the result that the armature flux is in effect pushed aside and the converter "slips a pole". The polarity at the same time is reversed.

Either of the two remaining rotaries is then started in a similar manner and finally put in series by means of switches which are so interlocked that the operator cannot connect any two machines in parallel on the direct current side.

The speed limit device must be tested so as to obtain proper operation before the machine on which it is to be installed is put into service.

The apparatus is protected on both sides of the machine with overload relays.

#### Specifications.

The specifications of all apparatus will be standard, only the performance being consid-



ered in this discussion.

#### Rotary Converter.

After a run of 24 hours at full load the temperature rise of the armature and field coils shall not be more than  $35^{\circ}$  C. The machine when operated at 150% overload shall not indicate a temperature rise of more than  $55^{\circ}$  C. after a two hour run.

Relative to overload capacity, the machine must be of such design as will carry a 50% overload without movement of the brushes and without injurious sparking, and an overload of 100% at full voltage momentarily without flashing over or injurious sparking.

The efficiency of the machine to be as follows:

150%	Full load	- - - -	97.0%
100%	" "	- - - -	96.5%
75%	" "	- - - -	96.0%
50%	" "	- - - -	94.5%



## Transformers.

After a run of 24 hours at full load, the rise of temperature of any part of the transformer shall not exceed  $35^{\circ}$  C. The transformer must be of such design as will carry an overload of 25% without greater rise of temperature than  $57^{\circ}$  C.

The efficiency is to be as follows:

150%	Full load	- - - -	98.3%
100%	" "	- - - -	98.3%
75%	" "	- - - -	98.2%
50%	" "	- - - -	97.8%
25%	" "	- - - -	96.2%



## TRANSMISSION LINE.

## Choice of Wire.

The distance between the power house and substation No. 5 is 63,000 feet. The load up to this station is 6250 K.W.

Assume the following:

Phases - - - - - 3  
 Receiver voltage 30000  
 Cycles - - - - - 25  
 Loss - - - - - 2%

Loss = 125 K.W.

Loss per wire = 46.1 K.W.

$I = 120$  amperes.

$R = 41600 \div 120^2 = 2.9$  ohms.

R per 1000 feet =  $2.9 \div 63 = 0.046$

Wire required: #0000 copper or 400,000  
 cir. mils aluminum.

Consider a #0000 copper wire.

Resistance per 1000 feet = 0.048

Line resistance =  $0.048 \times 63 = 3.2$

Power loss =  $120^2 \times 3.2 = 46,000$  watts.





Cost of 46 K.W. per year = \$4030.

Cost of 1000 feet #0000 wire = \$400.

Cost of 63,000 feet = \$25,200.

Interest and depreciation = \$1512.

Annual charge against copper = \$26,712.

Consider a #000 copper wire.

Resistance per 1000 feet = 0.06 ohms.

Line resistance = 3.78

Power loss = 54.4 K.W.

Cost of 54.4 K.W. per year = \$4660.

Annual charge against copper = \$23,956.

Saving on copper = \$26,712. - \$23,956 = \$2756.

Increase in cost of power = \$630.

Net saving = \$2756. - \$630. = \$2126.

Consider a #1 copper wire.

Resistance per 1000 feet = 0.1215

Line resistance = 7.65

Cost of power lost = \$9600.

Annual charge against copper = \$13,356.

A #2 copper wire indicates a small saving over the #1, but inasmuch as the current would not be well within the current carrying capacity



the #1 wire was selected as being the most economical size of wire as far as first cost and copper wire itself were concerned.

Consider a #000 aluminum wire.

Resistance per 1000 feet = 0.0996

Line resistance = 6.2

Power loss = 90.400 watts.

Cost of 90.4 K.W. per year = \$7920.

Cost of wire = \$13,800.

Annual charge against aluminum = \$14,628.

Consider a #00 aluminum wire.

Resistance per 1000 feet = 0.125

Line resistance 7.87

Power loss = 113,000

Cost of 113 K.W. per year = \$9900.

Cost of wire = \$11,500.

Annual charge = \$12,190.

Saving on aluminum = \$2438.

Increase in cost of power = \$1980.

Net saving of \$350.



The wires now considered are the #000 aluminum and the #1 copper. The relative costs are given below:

Wire	Cost of wire	Cost of power.	Total
#000 Al.	\$14,628.	\$7920.	\$22,548.
#1 Cu.	\$13,356.	\$9600.	\$22,956.

The #000 aluminum wire was selected because of its first cost; weight, a factor which determines the size of the towers or poles; and because of its greater tensile strength.

#### Spacing of Wires.

The wires are to be arranged in delta, 36 inches apart. ?

#### Capacity and Inductance per Wire.

The inductance per wire equals L.

$$L = 2 \left( \log_e \frac{2 + \frac{1}{4}}{r} - \log_e \frac{2}{D} \right)$$

$$L \text{ per foot} = L_1.$$

$$L_1 = 2 \times 12 \times 2.54 \left( \log_e \frac{2 \times 12}{.41} + \frac{1}{4} - \log_e \frac{24}{36} \right) 10^{-9}$$

$$= 264 \times 10^{-9} \text{ henrys.}$$

Length of line = 63,000 feet.

Inductance per wire = 0.01662 henry.



Capacity in farads per mile equals C.

$$C = \frac{38.8 \times 10^{-9}}{\log_{10} \frac{2D}{d}} = \frac{38.8 \times 10^{-9}}{\log_{10} \frac{72}{.41}}$$

$$= 17.4 \times 10^{-9} \text{ farads per mile.}$$

Therefore the line capacity to neutral is:

$$207 \times 10^{-9} \text{ farads.}$$

The natural period of the circuit is given by the equation:

$$\frac{2\pi\sqrt{LC}}{}$$

$$= 2 \times 3.1416\pi \sqrt{0.01662 \times 207 \times 10^{-9}}$$

$$= 0.00036.$$

Therefore there is no danger of resonance taking place.

The voltage at the generating station equals  $E_g$ .

$$E_g = E \cosh PS + z_0 I \sinh PS.$$

P = propagation constant.

$$P^2 = \sqrt{(r + jpL)(g + jpC)}$$

r - resistance per mile = 0.52

L - inductance per mile = 0.0014.

C - capacity per mile =  $17.4 \times 10^{-9}$





$$p = 2\pi f = 157$$

$$pL = .22$$

$$pC = .273 \times 10^{-5}$$

$$S = \text{distance in miles } 11.9$$

$$P = \sqrt{(52 j .22 + (0 j .273 \times 10^{-5})^2)}$$

$$.00154 \ 56^{\circ} \ 28'$$

$$\cosh P = \cosh x \cos y + j \sinh x \sin y$$

$$Z_o = \sqrt{\frac{r j p L}{g j p C}}$$

$$E_g = 17900$$

To check this value of  $E_g$  the following method has been used:

$$X_c = 10^9 / 2 \ 25 \times 207 = 30800$$

$$I_c = 30000 / 2 \times 30800 \times 1.73 = .282$$

$$RI_c = 6.18 \times .282 = 1.742$$

$$X_L I_c = 2.62 \times .282 = .738$$

$$RI = 6.18 \times 133.5 = 825$$

$$X I = 2.62 \times 133.5 = 350$$

From the diagram on page 34:

$$BA = 7451.2 + 350 = 7801.2$$

$$OB = 16373.5$$

Therefore,

$$OA = 18000$$







## POWER HOUSE.

### Location.

The power house designed to carry the load of the proposed electrification is to be located on the bank of Lake Michigan at a point near the city of Beach, 37 miles from Chicago. This location was found most suitable from the load conditions of the road and for operating facilities of the plant.

### Power Curve.

The capacity of the power house was determined from the load curve shown on plate 7. This load curve was obtained by finding the current taken by each car on the road, from the current curve for every ten minutes. The total current expressed in K.W. with an additional 19 K.W. per car to take care of heating, lighting, and air brake equipment, was plotted against time. This resultant curve constitutes the load curve.

From this curve the peak loads were found to be 14,500 K.W. and 14,000 K.W. occurring at



8:00 A.M. and 6:00 P.M., respectively, and the average minimum load to be about 2500 K.W. at 3:00 A.M.

The generating units were chosen so that the plant would operate at about the same efficiency for all loads. In order to make the plant flexible and accomplish the mentioned result the following units were selected: three 5000 K.W. and one 3000 K.W., making a total of 18,000 K.W. rated capacity. The additional capacity was provided to serve as a reserve in case of breakdown of some unit.

#### Equipment.

The driving units are high pressure turbines of the Curtis horizontal type, equipped with Wheeler surface condenser of 18,000 square feet for the 5000 K.W. units and 14,000 square feet for the 3000 K.W. units.

The condensing pumps are: circulating pump, 18-inch, D.A. Volute pump, turbine driven, 24-inch suction and discharge; hot well





pump, 23 inch, 2 stage, turbine driven; vacuum pump, Wheeler tandem rotary dry vacuum pump for 18,000 and 14,000 square feet condenser, respectively.

The exciters: one 200 K.W. 110 volt General Electric, driven by Curtis non-condensing steam turbine, and one 200 K.W. 110 volt motor driven.

One 40 ton Century Crane.

The transformers,  $K_2$  oil switches, low tension buses, and selector switches are located on the main floor at the side of the engine room. The  $H_6$  oil switches, high tension buses, and operating board are on the second floor. The lightning arresters, choke coils, and line outlets are on the third floor.

The rheostats and storage batteries are located on the basement floor.

#### Boiler Room.

The boiler equipment consists of 16- 750 boiler horsepower Babcock and Wilcox water tube boilers equipped with chain grate automatic



stokers and superheater, furnishing steam at 200 lbs. gauge and 150 degrees superheat.

The water heater: 1 #8 Stilwell, horizontal 1200 H.P. heater.

Boiler feed pumps: two Alberger turbine driven boiler feed pumps of 5000 boiler horse power capacity, operating in multiple.

The coal and ash handling equipment consists of two sets of bucket conveyors running parallel to the length of the boiler room. Each set of conveyors handles both coal and ash for one row of boilers. Coal bunkers of sufficient capacity are placed above the boiler settings and have gravity feed downspouts.

Chimneys: four 9-foot diameter brick chimneys, 150 feet high.

The over-all dimensions of the plant are: length: 212 feet; width: 197 feet; height: 64 feet.



## SWITCHBOARD.

The switch board is of the desk type. The operating stand is so situated that the operator has a clear view of the whole engine room. The instruments are above the operating stand.

The list of instruments is as follows:

- 7 D.C. Ammeters.
- 14 A.C. Ammeters.
- 3 D.C. Voltmeters.
- 5 A.C. Voltmeters.
- 4 Power factor indicators.
- 6 Indicating wattmeters.
- 4 Recording wattmeters.
- 1 Frequencymeter.

These instruments comprise the D.C. and A.C. sides of the operating board. The D.C. instruments are used for the field excitation and excitors.

The control is all of the remote type. For the low tension side there are:

- 11 K<sub>2</sub> Oil switches.
- 8 H<sub>3</sub> Oil switches.



4 Motor controlled governors.

6 Remote controlled rheostats.

The  $K_2$  and  $H_3$  oil switches and the circuit breakers are all solenoid operated. The engine governors are controlled from the operating stand through a small motor.

The general arrangement of the switchboard is made up of a storage battery panel for emergency, a steam driven exciter panel, an induction motor driven exciter panel, four steam driven generator panels, and one feeder panel. The battery panel has an ammeter and voltmeter with a switch and rheostat for charging or discharging the batteries. The steam driven exciter has an ammeter and voltmeter with circuit breaker control. For the induction motor starting, a compensator is used, giving half voltage for starting. This panel has an ammeter and voltmeter. The generator panels each have three ammeters, a voltmeter, power factor indicator, indicating wattmeter, and recording wattmeter. An overload signal lamp is also used. The feeder panels have two ammeters





and two indicating wattmeters, one ammeter and one wattmeter being used on each outgoing line. This is made possible by having a balanced load at all times, since all of the power is supplied to rotary converters.

The operating stand is 14 feet long, 5 feet wide, and 8 feet high. The desk stand is 2 feet 8 inches high at the front and 3 feet 4 inches high at the rear.

The voltage generated is 6600 volts and this is stepped up to 30,820 volts through three single phase transformers connected to each generator. The capacity of the transformers for the 3000 K.W. unit is 1000 K.W. each and for the 5000 K.W. unit is 1600 K.W. each.





















PLATE-6



POSITIVE FEEDERS  
FOR  
SUBSTATION NO. 1

PLATE 7  
POWER CURVE









LPH

2000 Pacific Wave  
PAGE 11






**SUB-STATION**  
 FOR  
**PROPOSED ELECTRIFICATION**  
 OF  
**THE MILWAUKEE BRANCH**  
**CHICAGO AND NORTHWESTERN RY.**  
**ARMOUR INSTITUTE OF TECHNOLOGY**  
 SCALE  $\frac{1}{4}'' = 2'$




- (V) POTENTIAL PLUS RECEIPTS
- (A) SYNCHRONIZING (S) BREAKERS
- (S) CENTRAL METERING
- (PF) REACTOR SIGNAL LIGHT
- (I.W.) OVERLOAD SIGNAL LIGHT
- (F) OVERLOAD SIGNAL LIGHT
- (S) OVERLOAD SIGNAL LIGHT

**POWER HOUSE SWITCH BOARD**  
 FOR  
**PROPOSED ELECTRIFICATION**  
 OF  
**THE MILWAUKEE BRANCH**  
**CHICAGO AND NORTHWESTERN RY.**  
**ARMOUR INSTITUTE OF TECHNOLOGY**  
 SCALE 1/2" = 1'





- KILHE PANEL
- A.T. HOISTING PANEL
- D. TOTAL LOAD PANEL
- A.M. AMMETER
- V. VOLTMETER
- C.C.M. CURVE DRAWING INSTRUMENT
- A.M.P. RECEIVING WATTMETER
- A.L. ALARM
- R.O.A. REMOTE CONTROL RING START
- M.I. INDICATING WATTMETER
- M. POWER FACTOR METER
- E.R.M. END PLAY MECHANISM
- S.L. SPEED LIMIT DEVICE
- R.L. RED LAMP
- G.L. GREEN LAMP
- O.L.R. OPER. LOCAL RELAY
- U.S. U.S. SWITCH
- W.F. FIELD PANEL
- R.B.L. FIELD BREAK UP SWITCH

**SUB-STATION WIRING DIAGRAM**  
 FOR  
**PROPOSED ELECTRIFICATION**  
 OF  
**THE MILWAUKEE BRANCH**  
**CHICAGO AND NORTHWESTERN RY.**  
**ARMOUR INSTITUTE OF TECHNOLOGY**











POWER HOUSE


PROPOSED ELECTRIFICATION


THE MILWAUKEE BRANCH  
CHICAGO AND NORTHWESTERN RY.  
ARMOUR INSTITUTE OF TECHNOLOGY


scale 1/4"

















POWER HOUSE  
FOR  
PROPOSED ELECTRIFICATION  
OF  
THE MILWAUKEE BRANCH  
CHICAGO AND NORTHWESTERN RY.  
ARMOUR INSTITUTE OF TECHNOLOGY  
SCALE 1/2" = 1'









ANTENNA WIRING IN 2500 CYCLE SPARK




ANTENNA WIRING IN 4000 CYCLE SPARK



ANTENNA WIRING IN 10000 CYCLE SPARK

POWER HOUSE WIRING DIAGRAM  
 FOR  
 PROPOSED ELECTRIFICATION  
 OF  
 THE MILWAUKEE BRANCH  
 CHICAGO AND NORTHWESTERN RY.  
 ARMOUR INSTITUTE OF TECHNOLOGY






DEERING

GRASS BANK

DEERING

GROSS PARK

CUYLER




WALKERSWOOD

SUMMERDALE

ROSE HILL

KENMORE




RAVENSWOOD

SAMMERDALE

ROSE HILL


NEW



KENMORE

ROGERS PARK


MAIN ST



TEMPLE ST EVANSTON

EVANSTON

CENTRAL EVANSTON



"Perfect" PROFILE PAPER MADE BY EUGENE DIETZGEN

"Perfect" PROFILE PAPER MADE BY EUGENE DIETZGEN




MAIN ST.

DEMPESTER ST.

EVANSTON


CENTRAL ST.



WINNETKA

NEWLWORTH

WINNETKA




Defeat PROFILE PAPER, PLATE A. EUGENE DIETZGEN Co.

Defeat PROFILE PAPER, PLATE A. EUGENE DIETZGEN Co.

CENTRAL ST. EVANSTON

WILMETTE

MENILWORTH




"Safecol" PROFILE PAPER. PLATE A.  
EUGENE DIEZIGEN Co.

"Safecol" PROFILE PAPER. PLATE A.  
EUGENE DIEZIGEN Co.


WINNETKA

HUBBARD WOODS



RAVINE

"Super" PROFILE PA... PLATE A.  
EUGENE DIST...




HIGHLAND PARK

HIGHLAND PARK


"Perfect" PROFILE PAPER, PLATE A.  
 EUGENE DIETZGEN CO.  
 EUGENE, OREGON


"Perfect" PROFILE PAPER, PLATE A.  
 EUGENE DIETZGEN CO.  
 EUGENE, OREGON




FORT SHERIDAN

LAKE FOREST








NORTH CHICAGO

WAUKEGAN


Perfect PROFILE PAPER. PLATE A.  
EUGENE DISTZGEN CO.  
EUGENE DISTZGEN CO.  
EUGENE DISTZGEN CO.

Perfect PROFILE PAPER. PLATE A.  
EUGENE DISTZGEN CO.  
EUGENE DISTZGEN CO.  
EUGENE DISTZGEN CO.






WAUKESHA




ZION CITY

Superficial PROFILE PAPER, PLATE A.  
EUGENE DIETRICH & Co.

Superficial PROFILE PAPER, PLATE A.  
EUGENE DIETRICH & Co.





CAMP LOBAN

WINTHROP HARBOUR







BERRYVILLE




SECTION

RACINE


RACINE JUNCTION

RACINE






COUNTY LINE





COUNTY LINE

CARTERSVILLE




SO. MILWAUKEE

SO. MILWAUKEE








ALLIS

MILWAUKEE



AMPERES	MILES PER HOUR
16.5	11
13.5	36
10.5	63
7.5	20
4.5	12
1.5	4

