PIPER AIRCRAFT CORPORATION

MODELS: Piper Cub E-2, 2 PO-CIM

I.C. NUMBER: ATC 455

Engine Continental A-40, A-40-2, A-40-3 (or A-40-4 on serial numbers 66, 72 and up having demountable engine mount) (A-40) (A-40-2) Maximum except take-off -- in.Hg., 2550 rpm (37 hp) Placard limits (A-40-3) Take-off (one minute) -- in.Hg., 2550 rpm (37 hp) (A-40-4) Maximum, except take-off -- in.Hg., 2575 rpm (40 hp) (A-40-4) Take-off (one minute) -- in. Hg., 2575 rpm (40 hp) Propeller boow Placard speeds Not required Fuel capacity 9 gallons (one tank in fuselage) Cil capacity 1 gallon No. passengers Baggage 5 lbs. (provided approved compartment is installed aft of cockpit - otherwise 0 lbs.) Weights Empty use actual (approximately 556 lbs. with Class I items) Standard 970 lbs. (+16) in. and (+20.5) C.G. limits Specification basis Approved Type Certificate No. 455 Serial numbers 26 and up manufactured prior to 3/24/37 eligible. Approval expired as of that date. EQUIPMENT: (Datum is rear of wing leading edge) (* Means net increase) Class I: 101. 7.00-4 wheels 102. Tail skid Class II: None Class III: 301. Cockpit enclosure 7 1bs. 302. Steerable tail wheel and 6.00-2 tire (Goodyear - Aircraft Associates installation, Drawing E-4)
(a) 8.00-4 wheels with 8.00-4 2-ply 3 lbs.* 303. tires (b) 16x7-3 wheels (Goodyear 3LNBM) No change in weight 304. Skis (a) Piper S-1000 (b) Air Transport A or 1220-480 Federal SA-1 (C) Marston MFS-1200 (d)

- NOTE 1. Manufacturer's serial numbers 66, 72 and up have demountable engine mount.
- NOTE 2. The wing spars on serial numbers 84 and up have straight butts with "U" shaped reinforcements instead of triangular shaped butts with hole drilled thru spar for fuselage attachment bolts.
- NOTE 3. The airplanes eligible are also approved with alternate seats, heel wells, and rudder pedals in accordance with Drawings J2-A46, J2-A62 and J2-A65. Installation may be made in field using parts furnished by manufacturer.
- NOTE 4. Eligible for export to all countries except Great Britain, Canada, and Australia (5/14/38).