

SLM


2-8-2 Electric Locomotive for single-phase current, for the Rhaetian Railway (Switzerland)

Locomotive à courant monophasé pour le Chemin de fer Rhétique (Suisse) □ □

Locomotiva elettrica a corrente monofase per la Ferrovia Retica (Svizzera) □ □

1 D 1 Einphasen-Wechselstromlokomotive für die Rhätische Bahn (Schweiz) □ □

Gauge	Voie	1000 mm	Scartamento	Spurweite
Diameter of driving wheels	Diamètre des roues motrices	1070 "	Diametro delle ruote motrici	Triebrad-Durchmesser
" " carrying "	" " " porteuses	710 "	" " " portanti	Laufgrad- "
Rigid wheel base	Empattement fixe	1550 "	Passo rigido	Fester Radstand
Total " "	" total	8000 "	" totale	Totaler "
Number of motors	Nombre des moteurs	2	Numero dei motori	Anzahl Motoren
Effect of motors p. 1 hour	Puissance unihoraire des moteurs	600 HP	Potenza dei motori per ora	Stundenleistung der Motoren
Maximum speed	Vitesse maximum	45 km/h	Velocità massima	Fahrgeschwindigkeit (max.)
Tractive power (max.)	Effort de traction (max.)	8400 kg	Sforzo di trazione (massimo)	Zugkraft (max.)
Weight in working order	Poids de la machine en service	55,17 t	Peso della locomotiva in servizio	Gewicht der Maschine im Dienst



SOCIÉTÉ SUISSE POUR LA CONSTRUCTION
DE LOCOMOTIVES ET DE MACHINES
WINTERTHUR

L 449

LO. 4449 (1) SWISS
LOCOMOTIVE AND MACHINE WORKS
WINTERTHUR