

# Functions & Pointers (1B)

Copyright (c) 2009-2016 Young W. Lim.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

### f3.c

```
#include <stdio.h>

void func(int *x) {
    printf("&x= %p x= %p *x= %d \n", &x, x, *x);
    *x *= 2;
    printf("&x= %p x= %p *x= %d \n", &x, x, *x);
}

void main(void) {
    int a = 100;

    printf("&a= %p a= %d \n", &a, a);

    func( &a );

    printf("&a= %p a= %d \n", &a, a);
}
```

```
&a= 0xbfa7d7fc a= 100
&x= 0xbfa7d7e0 x= 0xbfa7d7fc *x= 100
&x= 0xbfa7d7e0 x= 0xbfa7d7fc *x= 200
&a= 0xbfa7d7fc a= 200
```

#### f4.c

```
#include <stdio.h>

int sum(int x[], int n) {
    int i, S=0;
    for (i=0; i<n; ++i) S += x[i];
    return S;
}

int main(void) {
    int i, j;
    int a[3][4] = {{ 1, 2, 3, 4}, { 5, 6, 7, 8}, { 9, 10, 11, 12}};

    int S0, S1, S2;

    S0 = sum( a[0], 4 );
    S1 = sum( a[1], 4 );
    S2 = sum( a[2], 4 );

    printf("Sum of 1st row of a = %d \n", S0);
    printf("Sum of 2nd row of a = %d \n", S1);
    printf("Sum of 3rd row of a = %d \n", S2);
}
```

**f4.c**



**f4.c**

