

# R Introduction

Young W. Lim

2024-07-22 Mon

- 1 Based on
- 2 Introcuton B
  - Introduction

## "An Introduction to R" Notes on R: A Programming Environment for Data Analysis and Graphics

W. N. Venables, D. M. Smith, and the R Core Team

I, the copyright holder of this work, hereby publish it under the following licenses: GNU head Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled GNU Free Documentation License.

CC BY SA This file is licensed under the Creative Commons Attribution ShareAlike 3.0 Unported License. In short: you are free to share and make derivative works of the file under the conditions that you appropriately attribute it, and that you distribute it only under a license compatible with this one.

# Data permanency and removing objects (1)

- the entities that **R** creates and manipulates are known as **objects**
  - variables
  - arrays of numbers
  - character strings
  - functions
  - more general structures built from such components
- during an R session, objects are created and stored by name

[https://www.w3schools.com/statistics/statistics\\_statistical\\_inference.php](https://www.w3schools.com/statistics/statistics_statistical_inference.php)

## Data permanency and removing objects (2)

- The R command  
`> objects()`  
(alternatively, `ls()`) can be used to display the names of (most of) the objects which are currently stored within R.
- the collection of **objects** currently stored is called the **workspace**

[https://www.w3schools.com/statistics/statistics\\_statistical\\_inference.php](https://www.w3schools.com/statistics/statistics_statistical_inference.php)

# Types of R objects (1-1)

- a **vector** is an ordered collection of numerical, character, complex or logical objects.  
vectors are collection of atomic component or **modes** the same data type
- a **matrix** is a multidimensional collection of data entries of the same type.  
matrices have two dimensions.  
rownames and colnames

[https://www.w3schools.com/statistics/statistics\\_statistical\\_inference.php](https://www.w3schools.com/statistics/statistics_statistical_inference.php)

# Types of R objects (1-2)

- a **list** is an ordered collection of objects that can be of different **modes**  
different data types
- though a **data.frame** is a restricted **list** with class **data.frame**, it may be regarded as a **matrix** with columns that can be of different modes.  
It is displayed in matrix form, rows by columns.  
(Its like an excel spreadsheet)
- A **data.frame** is a list of variables of the same number of rows with unique row names, given class **data.frame**  
if no variables are included,  
the row names determine the number of rows.

[https://www.w3schools.com/statistics/statistics\\_statistical\\_inference.php](https://www.w3schools.com/statistics/statistics_statistical_inference.php)

## Types of R objects (2)

- A **factor** is a vector of **categorical variables**, it can be ordered or unordered.
- **array** an array in R can have one, two or more dimensions. useful to store multiple related **data.frame** (for example when I jack-knife or permute data). Note if there are insufficient objects to fill the array, R recycles (see below)

[https://www.w3schools.com/statistics/statistics\\_statistical\\_inference.php](https://www.w3schools.com/statistics/statistics_statistical_inference.php)



# Dataframe and class objects in Python

- By definition, a class is a code template for creating objects.
- This means that you can define a class that will create a certain object for you when this class has been instantiated.
- Then, the **DataFrame** is a type of **pandas object**.
- Therefore, you can say there's the **pandas DataFrame class**, that is code template that can create a DataFrame for you.
  - **pandas** is a fast, powerful, flexible and easy to use open source **data analysis and manipulation tool**, built on top of the Python programming language.

<https://365datascience.com/question/difference-between-dataframe-and-class-object>

# Classes in R language (1)

- **Classes** and **Objects** are basic concepts of Object-Oriented Programming that revolve around the real-life entities.
- Everything in R is an **object**.
- An **object** is simply a data structure that has some **methods** and **attributes**.
- A **class** is just a blueprint or a sketch of these **objects**.
  - represents the set of properties or **methods** that are common to all **objects** of one type.

<https://www.geeksforgeeks.org/classes-in-r-programming/>

## Classes in R language (2)

- Unlike most other programming languages, R has a three-class system.
  - S3 class
  - S4 class
  - Reference class

<https://www.geeksforgeeks.org/classes-in-r-programming/>

# S3 Class (1)

- **S3** is the simplest yet the most popular OOP system
- lacks formal definition and structure
- an object of this type can be created by just adding an **attribute** to it.

<https://www.geeksforgeeks.org/classes-in-r-programming/>

## S3 Class (2)

- in S3 systems, **methods** don't belong to the **class**.
- they belong to **generic functions**
- means that we can't create our own **methods** here, as we do in other programming languages like C++ or Java.
- but we can define what a **generic method** (for example print) does when applied to our objects.

<https://www.geeksforgeeks.org/classes-in-r-programming/>

# S4 Class (1)

- Programmers of other languages like C++, Java might find S3 to be very much different than their normal idea of classes
  - as it lacks the structure that classes are supposed to provide.
- **S4** is a slight improvement over **S3**
  - its objects have a proper definition
  - gives a proper structure to its objects.

<https://www.geeksforgeeks.org/classes-in-r-programming/>

## S4 Class (2)

- As shown in the above example,
  - `setClass()` is used to define a class and
  - `new()` is used to create the objects.
- The concept of methods in **S4** is similar to **S3**, i.e., they belong to\* generic functions\*.

<https://www.geeksforgeeks.org/classes-in-r-programming/>

- **Reference Class** is an improvement over **S4 Class**.
- Here the **methods** belong to the **classes**.
- These are much similar to object-oriented classes of other languages.
- Defining a Reference class is similar to defining S4 classes.
- we use `setRefClass()` instead of `setClass()` and `"*fields*"` instead of `"*slots*"`.

<https://www.geeksforgeeks.org/classes-in-r-programming/>



# R Objects (1)

- Every programming language has its own **data types** to store values or any information so that the user can assign these **data types** to the variables and perform **operations** respectively.
- **Operations** are performed accordingly to the **data types**

<https://www.geeksforgeeks.org/r-objects/?ref=lbp>

## R Objects (2)

- These **data types** can be
  - character
  - integer
  - float
  - long
  - etc.
- Based on the **data type**,  
memory/storage is allocated to the variable.
  - for example, in C language
    - character variables are assigned with 1 byte of memory
    - integer variable with 2 or 4 bytes of memory
    - other data types have different memory allocation for them.

<https://www.geeksforgeeks.org/r-objects/?ref=lbp>

- Unlike other programming languages, variables are assigned to **objects** rather than **data types** in R programming.

<https://www.geeksforgeeks.org/r-objects/?ref=lbp>

# R Object Classes (1)

- R possesses a simple generic function mechanism which can be used for an object-oriented style of programming. Method dispatch takes place based on the class of the first argument to the generic function.

- Usage

```
class(x)
class(x) <- names
unclass(x)
inherits(x, name)
```

<https://www.math.ucla.edu/~anderson/rw1001/library/base/html/class.html>

# Attributes of R objects (1)

## ① Basic Attributes

- The most basic and fundamental properties of every objects is its **mode** and **length**
- these are intrinsic attributes of every object.  
Examples of **mode** are "logical", "numeric", "character", "list", "expression", "name/symbol" and "function".

[https://www.w3schools.com/statistics/statistics\\_statistical\\_inference.php](https://www.w3schools.com/statistics/statistics_statistical_inference.php)

# Attributes of R objects (2)

## ① Basic Attributes (continued)

- character: a character string
- numeric: a real number, which can be an integer or a double
- integer: an integer
- logical: a logical (true/false) value

[https://www.w3schools.com/statistics/statistics\\_statistical\\_inference.php](https://www.w3schools.com/statistics/statistics_statistical_inference.php)

# Attributes of R objects (3)

- 1 Basic Attributes
- 2 Other Attributes, dimension

Object	Modes
vector	numeric, character, complex or logical
matrix	numeric, character, complex or logical
list	numeric, character, complex, logical, function, expression, ...
data frame	numeric, character, complex or logical
factor	numeric or character
array	numeric, character, complex or logical

- Whether object allows elements of different modes. For example all elements in a vector or array have to be

of the same mode. Whereas a list can contain any type of object including a list.