

Logic Background (1A)

Copyright (c) 2014 – 2018 Young W. Lim.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

This work is based on 6.825:

Techniques in Artificial Intelligence - courses - MIT

<https://courses.csail.mit.edu/6.825/>

Please send corrections (or suggestions) to youngwlim@hotmail.com.

This document was produced by using LibreOffice.

Proposition : etymology

From Old French, from Latin *prōpositiō*
 (“a **proposing**, design, theme, case”).

The content of an assertion

that may be taken as being **true** or **false**
and is considered abstractly without reference to
the linguistic sentence that constitutes the assertion.

Predicate : etymology

From Middle French predicate (French prédicat),
from post-classical Late Latin praedicatum (“**thing said of a subject**”),
a noun use of the neuter past participle of praedicare (“**proclaim**”)

From Latin predicātus, perfect passive participle of praedicō,
from prae + dicō (“**declare, proclaim**”), from dicō (“say, tell”).

Proposition

In Aristotelian logic a proposition is a particular kind of sentence, one which **affirms** or **denies** a **predicate** of a subject.

In formal logic a proposition is considered as objects of a formal language. A formal language begins with different types of **symbols**.

Predicate

(grammar) The part of the sentence (or clause) which states something about the subject or the object of the sentence.

<u>The dog</u>	<u>barked very loudly</u>
<i>subject</i>	<i>predicate</i>

(logic) A term of a statement, where the statement may be true or false depending on whether the thing referred to by the values of the statement's variables has the property signified by that (predicative) term.

Propositional Logic

Propositional logic includes only

- operators and
- propositional constants

as symbols in its language.

The propositions in this language are

- propositional constants
considered atomic propositions
- composite propositions
recursive application of operators to propositions

Predicate Logic

Predicate logic include

- variables,
- operators,
- predicate and
- function symbols, and
- quantifiers

as symbols in their languages.

A Formal Language

Syntax – legal expressions

Semantics – the meaning of legal expressions

Proof System – a way of manipulating syntactic expressions
to get another syntactic expressions

Multiple Percepts → Conclusions

Current State, Operators → Next State Properties

Propositional Logic

Sentences (WFFs : Well Formed Formulas)

T and F are **sentences**

Propositional variables are **sentences** (A, B, C, ...)

If A and B are sentences, the followings are also sentences

(A), $\neg A$, $A \wedge B$, $A \vee B$, $A \rightarrow B$, $A \leftrightarrow B$

Precedence of Connectives

\neg highest

\wedge

\vee

\Rightarrow

\Leftrightarrow lowest

$$A \vee B \wedge C = A \vee (B \wedge C)$$

$$A \wedge B \Rightarrow C \vee D = (A \wedge B) \Rightarrow (C \vee D)$$

$$A \Rightarrow B \vee C \Leftrightarrow D = (A \Rightarrow (B \vee C)) \Leftrightarrow D$$

Semantics

Meaning of a sentence : **true** or **false**

Interpretation : an assignment of **true** or **false**
to the **propositional variables**

$\models_i \varphi$: **Sentence** φ is true in the interpretation **i**

$\not\models_i \varphi$: **Sentence** φ is false in the interpretation **i**

Semantic Rules

$\models_i \phi$: **Sentence** ϕ is true in the interpretation \mathbf{i}

$\models_i \phi$: **Sentence** ϕ is true in the interpretation \mathbf{i}

$\models_i \mathbf{T}$ for all \mathbf{i}

$\not\models_i \mathbf{F}$ for all \mathbf{i}

$\models_i \mathbf{T}$ for all \mathbf{i}

Since \mathbf{i} is a mapping from variables to truth values,
Look \mathbf{P} up in \mathbf{i} and return the truth value assigned to \mathbf{P}

$\models_i \neg\phi$ iff $\not\models_i \phi$

$\models_i \phi \wedge \psi$ iff $\models_i \phi$ **and** $\models_i \psi$

$\models_i \phi \vee \psi$ iff $\models_i \phi$ **or** $\models_i \psi$


$\models_i \mathbf{P}$ iff $\mathbf{i}(\mathbf{P}) = \mathbf{T}$

Semantics

Meaning of a sentence : **true** or **false**

Interpretation : an assignment of **true** or **false**

to the **propositional variables** (P, Q, R)



Valid, Satisfiable, Unsatisfiable

A sentence is **valid** iff

Its truth value is **T** in all interpretations

ex) $\mathbf{T}, \neg\mathbf{F}, P \vee \neg P$ (**tautology: \top**)

A sentence is **satisfiable** iff

Its truth value is **T** in at least one interpretation

ex) $P, \mathbf{T}, \neg P$

A sentence is **unsatisfiable** iff

Its truth value is **F** in all interpretations

ex) $\mathbf{F}, \neg\mathbf{T}, P \wedge \neg P$ (**contradiction: \perp**)

Models


Semantics :

The relationship between **sentences** and **interpretations**

There are some **set of interpretations** that makes **a sentence true** → **models** of a sentence



An interpretation is a **model** of a sentence
if the **sentence** is **true** in that **interpretation**

An **interpretation i** is a **model** of a **sentence ϕ** **iff** $\models_i \phi$



Models

An interpretation i is a **model** of a sentence φ **iff** $\models_i \varphi$



Models and Interpretations

models

8 interpretations

P	Q	R	$P \wedge (Q \vee R)$
T	T	T	T
T	T	F	T
T	F	T	T
T	F	F	F
F	T	T	F
F	T	F	F
F	F	T	F
F	F	F	F

T	T	T
T	T	F

T	T	T
T	F	T

T	F	T
---	---	---

Entailment

An interpretation i is a **model** of a sentence φ **iff** $\models_i \varphi$


A set of sentences KB **entails** a sentence φ
iff every **model** of KB is also a **model** of φ

KB: Knowledge Base
a set of **sentences**

every model of KB


**every model of
each sentence in KB**

the model of a sentence φ




Models


A set of sentences KB **entails** a sentence φ
iff every **model** of KB is also a **model** of φ



U: A set of all possible interpretation



Entailment



References

- [1] en.wikipedia.org
- [2] en.wiktionary.org
- [3] U. Endriss, "Lecture Notes : Introduction to Prolog Programming"
- [4] <http://www.learnprolognow.org/> Learn Prolog Now!
- [5] http://www.csupomona.edu/~jrfisher/www/prolog_tutorial
- [6] www.cse.unsw.edu.au/~billw/cs9414/notes/prolog/intro.html
- [7] www.cse.unsw.edu.au/~billw/dictionaries/prolog/negation.html
- [8] <http://ilppp.cs.lth.se/>, P. Nugues, `An Intro to Lang Processing with Perl and Prolog