

Link 5. Search Libraries (II) Using RPATH

Young W. Lim

2023-04-27 Sat

1 Based on

2 Search libraries (II)

- `-rpath-link`
- `-rpath`
- `LD_RUN_PATH`
- BFD linkers
- Gold linkers

"Study of ELF loading and relocs", 1999

http://netwinder.osuosl.org/users/p/patb/public_html/elf_relocs.html

I, the copyright holder of this work, hereby publish it under the following licenses: GNU head Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled GNU Free Documentation License.

CC BY SA This file is licensed under the Creative Commons Attribution ShareAlike 3.0 Unported License. In short: you are free to share and make derivative works of the file under the conditions that you appropriately attribute it, and that you distribute it only under a license compatible with this one.

Compiling 32-bit program on 64-bit gcc

- `gcc -v`
- `gcc -m32 t.c`
- `sudo apt-get install gcc-multilib`
- `sudo apt-get install g++-multilib`
- `gcc-multilib`
- `g++-multilib`
- `gcc -m32`
- `objdump -m i386`

-rpath-link

- `rpath-link` DIR
 - when using ELF or SunOS, one shared library may require *another*
 - this happens when an `ld -shared` link includes a shared library as one of the input files.
 - may specify a sequence of directory names
 - by specifying a list of names separated by colons, or
 - by appearing multiple times

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

- `rpath-link` DIR
 - when the linker encounters such a dependency when doing a non-shared, non-relocateable **link**, it will automatically try to *locate* the required shared library and include it in the link, if it is not included explicitly.
- in such a case, the `-rpath-link` option specifies the first set of directories to search.

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

- the linker uses the following search paths to locate required shared libraries.
 - 1 Any directories specified by `-rpath-link` options.
 - 2 Any directories specified by `-rpath` options.
 - 3 On an ELF system, if the `-rpath` and `-rpath-link` options were not used, search the contents of the environment variable `LD_RUN_PATH`

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

- The difference between `-rpath` and `-rpath-link`
 - directories specified by `-rpath` options are included in the executable and used at runtime,
- the `-rpath-link` option is only effective at link time

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

- the linker uses the following search paths to locate required shared libraries.
 - ① On SunOS, if the `-rpath` option was not used, search any directories specified using `-L` options.
 - ② For a native linker, the contents of the environment variable `LD_LIBRARY_PATH`
 - ③ The default directories, normally `/lib` and `/usr/lib`
- If the required shared library is not found, the linker will issue a warning and continue with the link.

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

(1) informs the linker

- The `-rpath-link=dir` option tells the linker that when it encounters an input file that requests **dynamic dependencies** it should search `dir` to resolve them.
- `libfoobar.so` needs `libfoo.so` and `libbar.so`
 - if `rpath-link` is used,
 - no need to specify **dynamic dependencies**
 - no need to know what they are
 - no need to use `-lfoo -lbar`

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

(2) dynamic dependencies in .dynamic section

- the **dynamic dependencies** is defined in the **.dynamic** section of `libfoobar.so`
 - (NEEDED shared library file names)
 - therefore, just need to provide a directory where the required shared libraries can be found

```
$ readelf -d libfoobar.so
```

```
Dynamic section at offset 0xdf8 contains 26 entries:
```

Tag	Type	Name/Value
0x0000000000000001	(NEEDED)	Shared library: [libfoo.so]
0x0000000000000001	(NEEDED)	Shared library: [libbar.so]
0x0000000000000001	(NEEDED)	Shared library: [libc.so.6]
...		
...		

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

(3) the loader at runtime

- But does `-rpath-link=dir` give us a executable prog? – No.

```
$ ./prog
./prog: error while loading shared libraries: libfoobar.so: \
cannot open shared object file: No such file or directory
```

- at runtime, `libfoo.so`, `libbar.so`, and `libfoobar.so` might not be where they were linked
- but the loader might be able to locate them by other means:
 - through the `ldconfig` cache
 - by setting the `LD_LIBRARY_PATH` environment variable

```
$ export LD_LIBRARY_PATH=.; ./prog
foo
bar
```

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

(4) effective at link time

- `-rpath-link=dir` gives the linker (ld) the information that the loader (ld.so) would need to resolve some of the **dynamic dependencies** of prog at runtime
 - directories specified by `-rpath` options are *included* in the executable and *used* at runtime,
 - the `-rpath-link` option is only *effective* at link time

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

(5) no need using `-l` options

- assuming the **dynamic dependencies** *remained* true at runtime
- but it doesn't write that information into the **.dynamic** section of `prog`
- it just lets the linkage succeed, without spelling out all the recursive dynamic dependencies of the linkage by using `-l` options

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

-rpath-link (5)

- `rpath=dir`
 - provides the linker with the same information as `rpath-link=dir` does
 - instructs the linker to bake that information into the `.dynamic` section of the output file
(`DT_RPATH` / `DT_RUNPATH` entry in `.dynamic` section)

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

-rpath-link (6-1)

- by using `-rpath=$(pwd)`, `prog` contains the information that `$(pwd)` is a **runtime search path** for shared libraries that it depends on

```
$ export LD_LIBRARY_PATH=
$ gcc -o prog main.o -L. -lfoobar -Wl,-rpath=$(pwd)
$ ./prog
foo
bar
```

- as we can see:

```
$ readelf -d prog
```

Dynamic section at offset 0xe08 contains 26 entries:

Tag	Type	Name/Value
0x0000000000000001	(NEEDED)	Shared library: [libfoobar.so]
0x0000000000000001	(NEEDED)	Shared library: [libc.so.6]
0x000000000000000f	(RPATH)	Library rpath: [/home/imk/develop/so/scrap]
...	
...		

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-link>

-rpath-link (6-2)

- That search path will be tried (RPATH) `/home/imk/develop/so/scrap` after the directories listed in `LD_LIBRARY_PATH`, if any are set, and before the system defaults- the `ldconfig`-ed directories, plus `/lib` and `/usr/lib`

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

-rpath

-rpath (1)

- **rpath** designates the **run-time** search path *hard-coded* in an executable file or library
- **dynamic linking loaders** use the **rpath** to find required libraries.
 - **dynamic linking** is a sort of “lazy” linking of required shared libraries not during the stage of **compiling** but the later stage of **running** an executable.
- the **rpath** can be *stored there* at **link** time by the **linker**

https://en.wikipedia.org/wiki/Rpath#end_src

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- Specifically, it *encodes* a path to shared libraries into the header of an executable (or another shared library).
- this **RPATH header** value (so named in the ELF header standards) may either *override* or *supplement* the system default dynamic linking search paths.

https://en.wikipedia.org/wiki/Rpath#end_src

- The `rpath` of an executable or shared library is an *optional entry* in the `.dynamic` section of the `ELF` executable or shared libraries, with the type `DT_RPATH`, called the `DT_RPATH` attribute
- tools such as `chrpath` and `patchelf` can *create* or *modify* the entry `DT_RPATH` later.

https://en.wikipedia.org/wiki/Rpath#end_src

rpath and runpath (1)

- **rpath** and **runpath** are the most complex items in runtime search path
- the **rpath** and **runpath** of an executable or shared library are *optional entries* in the **.dynamic** section
- they are both a list of directories to search for

Name	Value	d_un	Executable	Shared Object
DT_RPATH*	15	d_val	optional	ignored
DT_RUNPATH	29	d_val	optional	optional

<https://refspecs.linuxbase.org/elf/gabi4+/ch5.dynamic.html>

rpath and runpath (2)

- The only difference between **rpath** and **runpath** is the order they are searched in.
- Specifically, their relation to **LD_LIBRARY_PATH**
 - **rpath** is searched in before **LD_LIBRARY_PATH**
 - **runpath** is searched in after **LD_LIBRARY_PATH**
- ① search **rpath**
- ② search **LD_LIBRARY_PATH**
- ③ search **runpath**
- **rpath** cannot be changed dynamically
- **runpath** can be changed dynamically with environment variables

<https://refspecs.linuxbase.org/elf/gabi4+/ch5.dynamic.html>

rpath and runpath (3)

- The ld dynamic linker does not search DT_RUNPATH locations for transitive dependencies, unlike DT_RPATH. [3]
- Instead of specifying the -rpath to the linker, the environment variable LD_RUN_PATH can be set to the same effect.

https://en.wikipedia.org/wiki/Rpath#end_src

Displaying RPATH / RUNPATH

- `readelf -d <binary_name> | grep 'R.*PATH'`
 - displays the RPATH or RUNPATH of a binary file.
 - In gcc, for instance, one could specify RPATH by `-Wl,-rpath,/custom/rpath/`

https://en.wikipedia.org/wiki/Rpath#end_src

--inhibit-rpath LIST

- the option `--inhibit-rpath LIST` of the dynamic linker instructs it to ignore `DT_RPATH` and `DT_RUNPATH` attributes of the **object names** in `LIST`.
- to specify a main program in the `LIST`, give empty string

https://en.wikipedia.org/wiki/Rpath#+end_src

LD_PRELOAD environment variable

- libraries specified by the environment variable LD_PRELOAD and then those listed in /etc/ld.so.preload are loaded before the search begins.
- a preload can thus be used to replace some (or all) of the requested library's normal functionalities, or it can simply be used to supply a library that would otherwise not be found.
- **static libraries** are searched and linked into the ELF file at **link** time and are not searched at **run** time.

https://en.wikipedia.org/wiki/Rpath#+end_src

--enable-new-dtags (1)

- The GNU Linker (`ld`) implements a feature which it calls `new-dtags`, which can be used to insert an `rpath` that has lower precedence than the `LD_LIBRARY_PATH` environment variable.

https://en.wikipedia.org/wiki/Rpath#end_src

--enable-new-dtags (2)

- If the `new-dtags` feature is enabled in the linker (`--enable-new-dtags`), GNU `ld`, besides setting the `DT_RPATH` attribute, also sets the `DT_RUNPATH` attribute to the same string. At run time, if the dynamic linker finds a `DT_RUNPATH` attribute, it ignores the value of the `DT_RPATH` attribute, with the effect that `LD_LIBRARY_PATH` is checked first and the paths in the `DT_RUNPATH` attribute are only searched afterwards.

https://en.wikipedia.org/wiki/Rpath#end_src

- If an object file participates in **dynamic linking**, its **program header table** will have an element of type **PT_DYNAMIC**.
- this **segment** contains the **.dynamic section**
- a special symbol, **_DYNAMIC**, labels the section, which contains an array of the following structures

<https://refspecs.linuxbase.org/elf/gabi4+/ch5.dynamic.html>

Dynamic structure

```
typedef struct {
    Elf32_Sword    d_tag;
    union {
        Elf32_Word    d_val;
        Elf32_Addr    d_ptr;
    } d_un;
} Elf32_Dyn;

extern Elf32_Dyn  _DYNAMIC[];

typedef struct {
    Elf64_Sxword    d_tag;
    union {
        Elf64_Xword    d_val;
        Elf64_Addr    d_ptr;
    } d_un;
} Elf64_Dyn;

extern Elf64_Dyn  _DYNAMIC[];
```

- `d_tag` controls the interpretation of `d_un` (*union*)
- `d_val` these objects represent integer values with various interpretations.
- `d_ptr` these objects represent program virtual addresses

<https://refspecs.linuxbase.org/elf/gabi4+/ch5.dynamic.html>

Dynamic array tags d_tag of the .dynamic section (1)

Name	Value	d_un	Executable	Shared Object
DT_NULL	0	ignored	mandatory	mandatory
DT_NEEDED	1	d_val	optional	optional
DT_PLTRELSZ	2	d_val	optional	optional
DT_PLTGOT	3	d_ptr	optional	optional
DT_HASH	4	d_ptr	mandatory	mandatory
DT_STRTAB	5	d_ptr	mandatory	mandatory
DT_SYMTAB	6	d_ptr	mandatory	mandatory
DT_RELA	7	d_ptr	mandatory	optional
DT_RELASZ	8	d_val	mandatory	optional
DT_RELAENT	9	d_val	mandatory	optional
DT_STRSZ	10	d_val	mandatory	mandatory
DT_SYMENT	11	d_val	mandatory	mandatory
DT_INIT	12	d_ptr	optional	optional
DT_FINI	13	d_ptr	optional	optional
DT_SONAME	14	d_val	ignored	optional
DT_RPATH*.....	15.....	d_val.....	optional.....	ignored
DT_SYMBOLIC*	16	ignored	ignored	optional
DT_REL	17	d_ptr	mandatory	optional
DT_RELSZ	18	d_val	mandatory	optional
DT_RELENT	19	d_val	mandatory	optional

<https://refspecs.linuxbase.org/elf/gabi4+/ch5.dynamic.html>

Dynamic array tags d_tag of the .dynamic section (2)

Name	Value	d_un	Executable	Shared Object
DT_PLTREL	20	d_val	optional	optional
DT_DEBUG	21	d_ptr	optional	ignored
DT_TEXTREL*	22	ignored	optional	optional
DT_JMPREL	23	d_ptr	optional	optional
DT_BIND_NOW*	24	ignored	optional	optional
DT_INIT_ARRAY	25	d_ptr	optional	optional
DT_FINI_ARRAY	26	d_ptr	optional	optional
DT_INIT_ARRAYSZ	27	d_val	optional	optional
DT_FINI_ARRAYSZ	28	d_val	optional	optional
DT_RUNPATH.....	29.....	d_val.....	optional.....	optional.....
DT_FLAGS	30	d_val	optional	optional
DT_ENCODING	32	unspecified	unspecified	unspecified
DT_PREINIT_ARRAY	32	d_ptr	optional	ignored
DT_PREINIT_ARRAYSZ	33	d_val	optional	ignored
DT_LOOS	0x60000000	unspecified	unspecified	unspecified
DT_HIOS	0x6ffff000	unspecified	unspecified	unspecified
DT_LOPROC	0x70000000	unspecified	unspecified	unspecified
DT_HIPROC	0x7fffffff	unspecified	unspecified	unspecified

<https://refspecs.linuxbase.org/elf/gabi4+/ch5.dynamic.html>

- an example of readelf output with RUNPATH and \$ORIGIN:

Dynamic section at offset 0x210268 contains 30 entries:

Tag	Type	Name/Value
(d_tag)	(DT_RUNPATH)	(d_val)
0x0000000000000001d	(RUNPATH)	Shared library: [\$ORIGIN]

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- **DT_RPATH** element holds the string table offset of a null-terminated search library search path string
- the offset is an index into the table recorded in the **DT_STRTAB** entry.
- this entry is at level 2.
- its use has been superseded by **DT_RUNPATH**

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- **DT_RUNPATH** element holds the string table offset of a null-terminated library search path string
- the offset is an index into the table recorded in the **DT_STRTAB** entry.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- paths in `rpath` and `runpath` can be
 - 1 absolute (e.g., `/path/to/my/libs/`)
 - 1 relative to the current working directory (e.g., `.`)
 - 1 relative to the executable
by using the `$ORIGIN` variable
in the `rpath` definition:

`https://amir.rachum.com/shared-libraries/`

\$ORIGIN (2)

- when the **dynamic linker** loads an object that uses \$ORIGIN, it must calculate the pathname of the directory containing the object
- the pathname will contain
 - no symbolic links
 - no use of `.` or `..` components.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

\$ORIGIN (3)

- within a string provided by dynamic array entries with the `DT_NEEDED` or `DT_RUNPATH` tags and in pathnames passed as parameters to the `dlopen()` routine, a dollar sign (`$`) introduces a **substitution sequence**.
- **substitution sequence** consists of the `$` sign immediately followed by
 - either the longest name sequence
 - or a name contained within `{` and `}`

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

\$ORIGIN (4)

- If the name is **ORIGIN**, then the **dynamic linker** replaces the **substitution sequence** with the absolute pathname of the directory containing the object which the **substitution sequence** originated.
- Otherwise (when the name is not **ORIGIN**) the behavior of the **dynamic linker** is unspecified

https://refspecs.linuxbase.org/elf/gabi4+/ch5.dynamic.html#shobj_dependencies

how to *check* the value of RPATH / RUNPATH

- `$ objdump -x path/to/executable | grep RPATH`
- `$ readelf -d path/to/executable | head -20`
- `$ chrpath -l path/to/executable`

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

how to set the value of RPATH / RUNPATH (1)

- during **compilation** time, use `configure -rpath=`

```
$ ./configure LDFLAGS=-Wl,-rpath=$ORIGIN/lib_path
```

- this will tell the **linker** to build and run the **executable** under the *specified* library path, usually used to override the *default* library paths.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

how to set the value of RPATH / RUNPATH (2)

- after **compilation** before **execution**

```
$ chrpath -r “\$\ORIGIN/lib_path” <executable>
```

- this command could fail
if no **rpath** was set previously for the executable.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

how to set the value of RPATH / RUNPATH (3)

- try below command with patchelf utility, which won't complain about an unset **rpath**, and will get **RUNPATH** set to achieve similar target.

```
$ patchelf --set-rpath '$ORIGIN/lib_path' <executable>
```

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- `objdump -x`
 - display all available *header* information, including the symbol table and relocation entries
 - Using `-x` is equivalent to specifying all of
 - `-a` archive header information
 - `-f` file headers, summary from the overall header
 - `-h` section header
 - `-p` private headers, specific to the object file format
 - `-r` relocation entries
 - `-t` symbol table entries

`objdump man page`

- `readelf -d`
 - displays the contents of the file's dynamic section, if it has one.

`readelf man page`

Configure the software (1)

- The configure script is responsible for getting ready to build the software on your specific system.
- It makes sure all of the **dependencies** for the rest of the build and install process are available, and finds out whatever it needs to know to use those **dependencies**

<https://thoughtbot.com/blog/the-magic-behind-configure-make-make-install>

Configure the software (2)

- Unix programs are often written in C, so we'll usually need a C compiler to build them.
- in these cases the configure script will establish that your system does indeed have a C *compiler*, and find out what it's *called* and where to *find* it.

<https://thoughtbot.com/blog/the-magic-behind-configure-make-make-install>

Build the software

- Once configure has done its job, we can invoke **make** to build the software.
- this runs a series of tasks defined in a **Makefile** to build the finished program from its source code.
- The tarball you download usually doesn't include a finished **Makefile**.
- Instead it comes with a *template* called **Makefile.in** and the **configure script** produces a *customised* **Makefile** specific to your system.

<https://thoughtbot.com/blog/the-magic-behind-configure-make-make-install>

Install the software (1)

- when the software is built and ready to run, the files can be copied to their final destinations
- The `make install` command will copy
 - the built program, and
 - its libraries and
 - documentation,to the correct locations.

<https://thoughtbot.com/blog/the-magic-behind-configure-make-make-install>

Install the software (2)

- the program's binary will be copied to a directory on your **PATH**,
- the program's manual page will be copied to a directory on your **MANPATH**, and
- any other files it depends on will be safely stored in the appropriate place.

<https://thoughtbot.com/blog/the-magic-behind-configure-make-make-install>

Install the software (3)

- since the *install step* is also defined in the **Makefile**, where the software is installed can change based on options passed to the **configure script**, or things the **configure script** discovered about your system.
- depending on where the software is being installed, you might need escalated permissions for this step so you can copy files to system directories.
- Using **sudo** will often do the trick.

<https://thoughtbot.com/blog/the-magic-behind-configure-make-make-install>

Configure script

- a shell script (generally written by GNU **Autoconf**) that goes up and looks for software and even tries various things to see what works.
- it then takes its *instructions* from **Makefile.in** and *builds* **Makefile** (and possibly some other files) that work on the current system.

<https://tldp.org/LDP/LG/current/smith.html>

Configure, make, makeinstall

- You run `configure`, type `./configure`
this builds a new `Makefile`
- Type `make`
this *builds* the program.
look for the first target in `Makefile` and
do what the instructions said.
The expected end result would be to build an `executable program`
- Now, as root, type `make install`
this again invokes `make`,
finds the target install in `Makefile` and
copies files to the directories to install the program.

<https://tldp.org/LDP/LG/current/smith.html>

- PatchELF is a simple utility for modifying existing ELF executables and libraries.
 - can change the **dynamic loader** ("ELF interpreter") of executables
 - can change the RPATH of executables and libraries.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- patchelf

- `--set-rpath` RUNPATH

Change the DT_RUNPATH of the executable or library to RUNPATH

- `--add-rpath` RUNPATH

Add RUNPATH to the existing DT_RUNPATH of the executable or library.

- `--remove-rpath`

Removes the DT_RPATH or DT_RUNPATH entry of the executable or library.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- patchelf

- `--shrink-rpath`

Remove from the DT_RUNPATH or DT_RPATH all directories that do not contain a library referenced by DT_NEEDED fields of the executable or library.

For instance, if an executable references one library `libfoo.so`, has an RPATH `"/lib:/usr/lib:/foo/lib"`, and `libfoo.so` can only be found in `/foo/lib`, then the new RPATH will be `"/foo/lib"`.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- patchelf

- `--allowed-rpath-prefixes` PREFIXES

Combined with the "`--shrink-rpath`" option, this can be used for further rpath tuning.

for instance, if an executable has

an RPATH "`/tmp/build-foo/.libs:/foo/lib`",

it is probably desirable to keep the "`/foo/lib`" reference instead of the "`/tmp`" entry.

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- patchelf

- `--print-rpath`

- Prints the DT_RUNPATH or DT_RPATH for an executable or library.

- `--force-rpath`

- Forces the use of the obsolete DT_RPATH in the file instead of DT_RUNPATH.

- By default DT_RPATH is converted to DT_RUNPATH

<https://nehck10.medium.com/creating-relocatable-linux-executables-by-setting-rpath>

- `-rpath dir`
 - add a directory to the runtime library search path
 - used when linking an ELF executable with shared objects
 - also used when locating shared objects which are *needed* by shared objects explicitly included in the link see the description of the `-rpath-link` option.
 - all `-rpath` arguments are concatenated and passed to the **runtime linker**
 - the **runtime linker** uses them to locate shared objects at runtime

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

- `-rpath dir`
 - if `-rpath` is not used when linking an ELF executable, the contents of the environment variable `LD_RUN_PATH` will be used if it is defined.
 - if a `-rpath` option is used, the runtime search path will be formed exclusively using the `-rpath` options, ignoring the `-L` options.
 - this can be useful when using `gcc`, which adds many `-L` options which may be on NFS mounted filesystems.

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

- `-rpath dir`
 - for compatibility with other ELF linkers, if the `-R` option is followed by a directory name, rather than a file name, it is treated as the `-rpath` option.

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

LD_LIBRARY_PATH and LD_RUN_PATH (0)

LD_RUN_PATH	LD_LIBRARY_PATH
link time resolution	run time resolution
linker	dynamic loader

https://ftp.gnu.org/old-gnu/Manuals/ld-2.9.1/html_node/ld_3.html

LD_LIBRARY_PATH and LD_RUN_PATH (1)

LD_RUN_PATH is used for the *link time* resolution of libraries
LD_LIBRARY_PATH is used for *run time* resolution of libraries.

LD_RUN_PATH is used by the *linker* to specify
where to search libraries only at *run time*

LD_LIBRARY_PATH is used by the *dynamic loader* to specify
where to search the libraries required to *execute* the binary
(at the *run time* of the binary)

LD_RUN_PATH is the *runtime* library search path

LD_LIBRARY_PATH paths are *not* searched during *link time*

https://www.quora.com/What-is-the-difference-between-LD_LIBRARY_PATH-and-LD_RUN_PATH

LD_LIBRARY_PATH and LD_RUN_PATH (2)

- `LD_RUN_PATH` variable is used by the linker (`ld`) the same way as `-rpath` argument to `ld` is used
- `LD_RUN_PATH` is used if `-rpath` is not specified
- However, if some binary is linked `LD_RUN_PATH` is not used and `-rpath` is specified on `ld` command line and you want to change the paths used to look for libraries at run time, `LD_LIBRARY_PATH` variable must be specified which is used by the dynamic linker (`/lib/ld-linux.so.*`)

https://bugzilla.redhat.com/show_bug.cgi?id=20218

LD_LIBRARY_PATH and LD_RUN_PATH (3)

- When you use the `-l` option, you must inform the dynamic linker about the directories of the dynamically linked libraries that are to be linked with your program at execution
- The environment variable `LD_RUN_PATH` lets you do this at link time
- to set `LD_RUN_PATH`, list the colon separated absolute pathnames of the directories in the order you want them searched

```
LD_RUN_PATH=/home/mylibs  
export LD_RUN_PATH
```

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (4)

- the command:
`cc -static -fpic -o prog file1.c file2.c -L/home/mylibs -lfoo`
directs the dynamic linker to search for `libfoo.so` in `/home/mylibs` when you execute your program `prog`
- the dynamic linker searches the standard place by default, after the directories you have assigned to **LD_RUN_PATH**
- Note that as far as the dynamic linker is concerned, the standard place for libraries is `/usr/lib`.
- Any executable versions of libraries supplied by the compilation system kept in `/usr/lib`

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (5)

- The environment variable **LD_LIBRARY_PATH** lets you do the same thing at run time.
- Suppose you have moved libfoo.so to /home/sharedobs /home/mylibs → /home/sharedobs
- It is too late to change **LD_RUN_PATH**, at least without link editing your program again

```
LD_RUN_PATH=/home/sharedobs
export LD_RUN_PATH    (--> not woking)
```

- however, you can change **LD_LIBRARY_PATH**

```
LD_LIBRARY_PATH=/home/sharedobs
export LD_LIBRARY_PATH
```

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (6)

- compile command

```
cc -static -fpic -o prog file1.c file2.c -L/home/mylibs -lfoo
```

- now when you execute your program prog

- the dynamic linker

searches for `libfoo.so` first in `/home/mylibs`
and, not finding it there, in `/home/sharedobs`.

```
LD_RUN_PATH=/home/mylibs
```

```
LD_LIBRARY_PATH=/home/sharedobs
```

- the directory assigned to `LD_RUN_PATH` is searched before the directory assigned to `LD_LIBRARY_PATH`.

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (7)

- because the pathname of `libfoo.so` is not hard-coded in `prog`,
you can *direct* the dynamic linker to *search* a different directory when you execute your program. (`LD_LIBRARY_PATH`)
- You can move a dynamically linked library without breaking your application.

```
LD_RUN_PATH=/home/mylibs  
LD_LIBRARY_PATH=/home/sharedobs
```

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (8)

- You can set `LD_LIBRARY_PATH` *without* first having set `LD_RUN_PATH`
- once you have used `LD_RUN_PATH` for an application, the dynamic linker searches the specified directories whenever the application is executed
unless you have relinked the application in a different environment
 - first `LD_RUN_PATH`, then `LD_LIBRARY_PATH`
 - `LD_RUN_PATH` overrides `LD_LIBRARY_PATH`

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (9)

- can assign different directories to **LD_LIBRARY_PATH** whenever you execute the application.
- **LD_LIBRARY_PATH** directs the dynamic linker to search the assigned directories before it searches the standard place.
- directories, including those in the optional second list, are searched in the order listed.

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (10)

- when linking a set-user or set-group program, the dynamic linker ignores any directories that are not built into the dynamic linker.
- Currently, the only built-in directory is /usr/lib

http://osr507doc.sco.com/en/tools/ccs_linkedit_dynamic_dirsearch.html

LD_LIBRARY_PATH and LD_RUN_PATH (11)

- can use the environment variable `LD_LIBRARY_PATH` which takes a colon(:) separated list of directories, to add to the `link-editor's` library search path.
- In its most general form, `LD_LIBRARY_PATH` takes two directory lists separated by a semicolon(;)
 - The first list is searched before the list(s) supplied on the command-line
 - the second list is searched after

<https://docs.oracle.com/cd/E19455-01/816-0559/chapter2-48927/index.html>

LD_LIBRARY_PATH and LD_RUN_PATH (12)

- Here is the combined effect of setting `LD_LIBRARY_PATH` and calling the `link-editor` with several `-L` occurrences:

```
$ LD_LIBRARY_PATH=dir1:dir2;dir3
$ export LD_LIBRARY_PATH
$ cc -o prog main.c -Lpath1 ... -Lpath2 ... -Lpathn -lfoo
```

- the first path list `dir1:dir2`
 - the second path list `dir3`
- The effective search path will be

```
dir1:dir2:path1:path2... pathn:dir3:/usr/ccs/lib:/usr/lib.
```

<https://docs.oracle.com/cd/E19455-01/816-0559/chapter2-48927/index.html>

LD_LIBRARY_PATH and LD_RUN_PATH (13)

- If no semicolon(;) is specified as part of the **LD_LIBRARY_PATH** definition, the specified directory list is interpreted after any -L options (the second list)

```
$ LD_LIBRARY_PATH=dir1:dir2
$ export LD_LIBRARY_PATH
$ cc -o prog main.c -Lpath1 ... -Lpath2 ... -Lpathn -lfoo
```

- Here the effective search path will be

```
path1:path2... pathn:dir1:dir2:/usr/ccs/lib:/usr/lib.
```

<https://docs.oracle.com/cd/E19455-01/816-0559/chapter2-48927/index.html>

- This environment variable can also be used to augment the search path of the runtime linker (see "Directories Searched by the Runtime Linker" for more details).
- To prevent this environment variable from influencing the **link-editor**, use the **-i** option.

<https://docs.oracle.com/cd/E19455-01/816-0559/chapter2-48927/index.html>

Executable File (1)

- executable files of various formats can be directly executed by the CPU once loaded by a suitable executable loader, rather than being interpreted by other software

https://en.wikipedia.org/wiki/Comparison_of_executable_file_formats

Executable File (2)

- typical executables contain

- binary application code

- headers and tables

with relocation and fixup information

- various kinds of meta data

https://en.wikipedia.org/wiki/Comparison_of_executable_file_formats

Executable File Formats

- the examples executable file formats

PE	on Microsoft Windows
ELF	on Linux and most other versions of Unix
Mach-O	on macOS and iOS
MZ	on DOS

https://en.wikipedia.org/wiki/Comparison_of_executable_file_formats

BFD (Binary File Descriptor) (1)

- **BFD** is a package which allows applications to use the *same routines* to operate on object files whatever the **object file format**.
- **BFD** consists of two parts:
 - the **front end** - common for various object file formats
 - the **back ends** - one for each object file format
 - a *new object file format* can be supported simply by creating a new BFD back end and adding it to the library

https://ftp.gnu.org/old-gnu/Manuals/bfd-2.9.1/html_mono/bfd.html#SEC1

BFD (Binary File Descriptor) (2)

- the **front end** of **BFD** provides the interface to the user.
 - manages memory and various canonical data structures
 - decides which **back end** to use and when to call **back end** routines.
- the **back ends** provide **BFD** its view of the real world.
 - provides a set of calls which the **BFD front end** can use to maintain its canonical form
 - may keep around information for their own use, for greater efficiency.

https://ftp.gnu.org/old-gnu/Manuals/bfd-2.9.1/html_mono/bfd.html#SEC1

BFD (Binary File Descriptor) (3)

- to use the **BFD** library,
 - include `bfd.h`
 - link with `libbfd.a`
- **BFD** provides a common interface to the parts of an object file for a *calling application*
- when an application successfully opens a target file (object, archive, or whatever), a pointer to an internal structure is returned

https://ftp.gnu.org/old-gnu/Manuals/bfd-2.9.1/html_mono/bfd.html#SEC1

BFD (Binary File Descriptor) (4)

- this returned pointer points to a structure called `bfd`, described in `bfd.h`
- our convention is to call this pointer, a `BFD`, and instances of it within code, `abfd`.
- all operations on the target object file are applied as methods to the `BFD`
- the mapping is defined within `bfd.h` in a set of macros, all beginning with `bfd_` to reduce namespace pollution

https://ftp.gnu.org/old-gnu/Manuals/bfd-2.9.1/html_mono/bfd.html#SEC1

BFD Libraries (1)

- **BFD libraries** : the GNU Project's *main mechanism* for the portable manipulation of object files
 - as of 2003, it supports approximately 50 file formats for some 25 instruction set architectures.
- **BFD libraries**'s main clients

gas	GNU Assembler
gld	GNU Linker
binutil	other GNU Binary Utilities tools
gdb	the GNU Debugger

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

- the frequent need to tinker with the API to accommodate new systems' capabilities has tended to limit its use
- as a result, **BFD** is not distributed separately, but is always included with releases of **binutils** and **GDB**
- Nevertheless, **BFD** is a critical component in the use of GNU tools for **embedded systems** development

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

BFD linker (1)

- **ld** combines a number of *object* and *archive files*, relocates their data and ties up symbol references
- Usually the *last step* in compiling a program is to *run ld*
- **ld** accepts Linker Command Language files written in a superset of AT&T's **Link Editor Command Language** syntax, to provide *explicit* and *total control* over the linking process.

<https://manpages.debian.org/testing/binutils-common/ld.bfd.1.en.html>

- the general purpose **BFD libraries** allows **ld**
 - to read, combine, and write *object files* in many different formats
 - for example, COFF or a.out
 - to link different formats together to produce *any available kind* of object file
 - to read the structured data out of a **core dump**

<https://stackoverflow.com/questions/49138195/whats-the-difference-between-rpath-1>

- flexible
- providing diagnostic information
 - many linkers abandon execution immediately upon encountering an error;
 - whenever possible, **BFD ld** continues executing, allowing you to identify other errors (or, in some cases, to get an output file in spite of the error).

<https://manpages.debian.org/testing/binutils-common/ld.bfd.1.en.html>

gold linker (1)

- **gold** is a linker for **ELF** files.
 - became an official GNU package was added to **binutils** in March 2008 and first released in **binutils** version 2.19.
 - **gold** was developed by Ian Lance Taylor and a small team at Google
 - to make a linker that is faster than the GNU linker (**BFD** 1d), especially for large applications coded in C++.

[https://en.wikipedia.org/wiki/Gold_\(linker\)](https://en.wikipedia.org/wiki/Gold_(linker))

gold linker (2)

- Unlike the GNU linker, **gold** does not use the **BFD** library
 - *limits* the object file formats to **ELF** only
 - a *cleaner* and *faster* implementation may be possible without an additional abstraction layer
- **BFD** library was removed to create a new linker *from scratch* rather than incrementally improve the GNU linker
 - *fixes* some *bugs* in old `ld` that break ELF files in various minor ways.

[https://en.wikipedia.org/wiki/Gold_\(linker\)](https://en.wikipedia.org/wiki/Gold_(linker))

- To specify **gold** in a makefile, one sets the LD or LD environmental variable to `ld.gold`.
- to specify **gold** through a compiler option, one can use the gcc option `-fuse-ld=gold`

[https://en.wikipedia.org/wiki/Gold_\(linker\)](https://en.wikipedia.org/wiki/Gold_(linker))

- to use, instead of the default linker

<code>-fuse-ld=bfd</code>	use the bfd linker
<code>-fuse-ld=gold</code>	use the gold linker
<code>-fuse-ld=lld</code>	use the LLVM lld linker
<code>-fuse-ld=mold</code>	use the Modern Linker (mold)

<https://gcc.gnu.org/onlinedocs/gcc/Link-Options.html>

C Makefile variables

- commonly used variables in makefiles

CC	C compiler
LD	link editor / load
CPP	C preprocessor
CXX	a C++ compiler
AS	an assembly language compiler
AR	an archive-maintaining program

<https://stackoverflow.com/questions/8862450/in-makefiles-what-do-cc-and-ld-stand->

- The LLVM Project is a collection of modular and reusable compiler and toolchain technologies.
 - the name "LLVM" itself is not an acronym;
 - it is the full name of the project.
 - despite its name *Low Level Virtual Machine*, LLVM has little to do with traditional virtual machines.
 - the LLVM project has grown beyond its initial scope as it is no longer focused on traditional virtual machines.

<https://llvm.org/>

- On the front end,
the **LLVM compiler** infrastructure uses **clang**
 - a compiler for programming languages C, C++ and CUDA
 - to turn source code into an interim format
- On the back end
 - LLVM clang code generator turns the interim format into final machine code

<https://www.heavy.ai/technical-glossary/llvm>

- The compiler has five basic phases
 - Parsing : Groups the words and tokens from the lexical analysis into a form that makes sense.
 - Lexical Analysis : Converts program text into words and tokens (everything apart from words, such as spaces and semicolons)
 - Semantic Analyser : Identifies the types and logics of the programs.
 - Optimization : Cleans the code for better run-time performance and addresses memory-related issues.
 - Code Generation : Turns code into a binary file that is executable.

<https://www.heavy.ai/technical-glossary/llvm>

sub-project

LLVM Core

Clang

LLDB

libc++

compiler-rt

MLIR

OpenMP

polly

libclc

klee

LLD

BOLT

- Clang is an "LLVM native" C/C++/Objective-C compiler, which aims to deliver amazingly fast compiles, extremely useful error and warning messages and to provide a platform for building great source level tools.
- The Clang Static Analyzer and clang-tidy are tools that automatically find bugs in your code, and are great examples of the sort of tools that can be built using the Clang frontend as a library to parse C/C++ code.

<https://www.heavy.ai/technical-glossary/llvm>